

AMENDMENT UNDER 37 C.F.R. §1.111
U.S. Application No. 09/849,563
Attorney Docket No. A8807 / SVL920010036US1

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (currently amended): A method of processing an application request on an end user application and an application server comprising the steps of:
 - a) initiating the application request on the end user application in a first language with a first application program;
 - b) transmitting the application request to the application server and converting the application request from the first language of the first end user application to PL/I running on the application server;
 - c) processing said application request on the application server;
 - d) transmitting a response to the application request from the application server to the end user application, and converting the response to the application request from the PL/I running on the application server to the first language of the first end user application; and
 - e) wherein the end user application and the application server have at least one connector therebetween, and the steps of (i) converting the application request from the first language of the first end user application as a source language to the PL/I running on the application server as a target language, and (ii) converting a response to the application request from the PL/I running

AMENDMENT UNDER 37 C.F.R. §1.111
U.S. Application No. 09/849,563
Attorney Docket No. A8807 / SVL920010036US1

on the application server as a source language to the first language of the first end user application as a target language, each comprise the steps of:

- 1) invoking connector metamodels of respective source and ~~PL/I~~ target languages;
 - 2) populating the connector metamodels with metamodel ~~data~~ metadata of each of the respective source and ~~PL/I~~ target languages; and
 - 3) converting the source language to the ~~PL/I~~ target ~~target~~ language.
2. (original): The method of claim 1 wherein the end user application is a web browser.
3. (currently amended): The method of claim 2 wherein the end user application is connected to the application server through a web server, and the web server comprises ~~an~~ a connector.
4. (original): The method of claim 1 wherein the metamodel metadata comprises invocation metamodel metadata, application domain interface metamodel metadata, and type descriptor metamodel metadata.

AMENDMENT UNDER 37 C.F.R. §1.111
U.S. Application No. 09/849,563
Attorney Docket No. A8807 / SVL920010036US1

5. (original): The method of claim 4 wherein the invocation metamodel metadata is chosen from the group consisting of message control information, security data, transactional semantics, trace and debug information, pre-condition and post-condition resources, and user data.

6. (original): The method of claim 4 wherein the application domain interface metamodel metadata comprises input parameter signatures, output parameter signatures, and return types.

7. (original): The method of claim 4 wherein the application domain interface metamodel metadata further includes language metamodel metadata.

8. (currently amended): The method of claim 7 wherein the language metamodel metadata includes mappings between the source and target languages.

9. (original): The method of claim 8 wherein the source language is object oriented, and the language metamodel metadata maps encapsulated objects into code and data.

AMENDMENT UNDER 37 C.F.R. §1.111
U.S. Application No. 09/849,563
Attorney Docket No. A8807 / SVL920010036US1

10. (currently amended): The method of claim 9 wherein the language metamodel metadata maps object inheritances into references and pointers.

11. (currently amended): The method of claim 4 wherein the type descriptor metamodel metadata defines physical realizations, storage-~~mapping~~ mappings, data types, data structures, and realization constraints.

12. (original): The method of claim 1 wherein the transaction is a rich transaction comprising a plurality of individual transactions, and further comprising processing the plurality of individual transactions on one end user application and a plurality of application servers.

13. (original): The method of claim 12 comprising passing individual transactions among individual application servers.

14. (currently amended): A transaction processing system comprising a client, a server, and at least one connector therebetween,

a) the client having an end user application, and being controlled and configured to initiate an application request with the server in a first language with a first application program and to transmit the application request to the server;

b) the connector being configured and controlled to receive the application request from the client, convert the application request from the first language of the first end user application running on the client to ~~PL/I language~~-running on the server;

c) the server being configured and controlled to receive the converted application request from the connector and ~~processing-process~~ the ~~said~~ application request in ~~PL/I language~~ with a second application program residing on the server, and to thereafter transmit a response to the application request through the connector back to the first application program on the client;

d) the connector being configured and controlled to receive ~~a~~the response to the application request from the server, to convert ~~a~~the response to the application request from the ~~PL/I language~~-running on the ~~application~~-server to the first language of the first application program running on the client; and

e) wherein the connector between the client and the server is configured and controlled to (i) convert the application request from the first language of the client application on the client as a source language to the ~~PL/I language~~-running on the ~~application~~-server as a target language, and (ii) convert the response to the application request from the ~~PL/I language~~-running on the ~~application~~-server as a source language to the first language of the client application running on the client as a target language, each by a method comprising the steps of:

1) retrieving connector metamodels of respective source and target languages from a metamodel metadata repository;

- 2) populating the connector metamodels with metamodel ~~data~~metadata from the metamodel metadata repository for each of the respective source and target languages; and
- 3) invoking the retrieved, populated connector metamodels and converting the source language to the target language.

15. (original): The system of claim 14 wherein the end user application is a web browser.

16. (currently amended): The system of claim 15 wherein the end user application is connected to the ~~application~~ server through a web server, and the web server comprises ~~an~~a connector.

17. (original): The system of claim 14 wherein the metamodel metadata comprises invocation metamodel metadata, application domain interface metamodel metadata, and type descriptor metamodel metadata.

18. (original): The system of claim 17 wherein the invocation metamodel metadata is chosen from the group consisting of message control information, security data, transactional

semantics, trace and debug information, pre-condition and post-condition resources, and user data.

19. (original): The system of claim 17 wherein the application domain interface metamodel metadata comprises input parameter signatures, output parameter signatures, and return types.

20. (original): The system of claim 17 wherein the application domain interface metamodel metadata further includes language metamodel metadata.

21. (currently amended): The system of claim 20 wherein the language metamodel metadata includes mappings between the source and target languages.

22. (currently amended): The system of ~~claim 23~~ claim 21 wherein the source language is object oriented, and the language metamodel metadata maps encapsulated objects into code and data.

23. (currently amended): The system of claim 22 wherein the language metamodel metadata maps object inheritances into references and pointers.

24 (currently amended): The system of claim 18 wherein the type descriptor metamodel metadata defines physical realizations, storage ~~mapping mappings~~, data types, data structures, and realization constraints.

25. (currently amended): The system of claim 14 wherein said system has a plurality of ~~application~~ servers and is configured and controlled to process rich transactions.

26. (currently amended): A transaction processing system configured and controlled to interact with a client application, and comprising a ~~PL/I~~ server, and at least one connector between the server and the client application, ~~where the client has an end user application, and is controlled and configured to initiate an application request with the server in a first language with a first application program and to transmit the application request to the server,~~ wherein:

a) the client having an end user application, and being controlled and configured to initiate an application request with the server in a first language with a first application program and to transmit the application request to the server;

a)b) the connector being configured and controlled to receive an application request from the client, convert the application request from the first language of the first end user application running on the client to the PL/I language running on the server;

~~b)c)~~ the server being configured and controlled to receive the converted application request from the connector and process the ~~said~~ application request in the PL/I language with a second application program residing on the server, and to thereafter transmit a response to the application request through the connector back to the first application program on the client;

~~e)d)~~ the connector being configured and controlled to receive the response to the application request from the server, to convert ~~a~~ the response to the application request from the PL/I language running on the ~~application~~ server to the first language of the first application program running on the client; and

~~d)e)~~ wherein the connector between the client and the server is configured and controlled to (i) convert the application request from the first language of the client application on the client as a source language to the PL/I language running on the ~~application~~ server as a target language, and (ii) convert the response to the application request from the PL/I language running on the ~~application~~ server as a source language to the first language of the client application running on the client as a target language, each by a method comprising the steps of:

- 1) retrieving connector metamodel metadata of respective source and target languages from a metamodel metadata repository;
- 2) populating the connector metamodels with metamodel ~~data~~ metadata of each of the respective source and target languages from the metamodel metadata repository and invoking the retrieved, populated connector metamodels; and
- 3) converting the source language to the target language.

27. (original): The system of claim 26 wherein the end user application is a web browser.

28. (currently amended): The system of claim 27 wherein the end user application is connected to the ~~application~~ server through a web server, and the web server comprises ~~an~~ a connector.

29. (original): The system of claim 26 wherein the metamodel metadata comprises invocation metamodel metadata, application domain interface metamodel metadata, and type descriptor metamodel metadata.

30. (original): The system of claim 29 wherein the invocation metamodel metadata is chosen from the group consisting of message control information, security data, transactional semantics, trace and debug information, pre-condition and post-condition resources, and user data.

31. (original): The system of claim 29 wherein the application domain interface metamodel metadata comprises input parameter signatures, output parameter signatures, and return types.

AMENDMENT UNDER 37 C.F.R. §1.111
U.S. Application No. 09/849,563
Attorney Docket No. A8807 / SVL920010036US1

32. (original): The system of claim 29 wherein the application domain interface metamodel metadata further includes language metamodel metadata.

33. (currently amended): The system of claim 32 wherein the language metamodel metadata includes mappings between the source and target languages.

34. (original): The system of claim 33 wherein the source language is object oriented, and the language metamodel metadata maps encapsulated objects into code and data.

35. (currently amended): The method of claim 33 wherein the source language and the target language are different object oriented languages, and the language metamodel metadata maps encapsulated code and data between the source and target languages.

36. (currently amended): The system of claim 33 wherein the language metamodel metadata maps object inheritances into references and pointers.

37. (currently amended): The system of claim 29 wherein the type descriptor metamodel metadata defines physical realizations, storage-~~mapping~~ mappings, data types, data structures, and realization constraints.

38. (currently amended): The system of claim 26 wherein said system has a plurality of ~~application~~-servers and is configured and controlled to process rich transactions.

39. (currently amended): A program product comprising a computer-readable storage medium having invocation metamodel metadata, application domain interface metamodel metadata, and language metamodel metadata, and computer instructions for building a metamodel metadata repository of source and ~~PL/I~~-target language metamodel metadata.

40. (currently amended): The program product of claim 39 further comprising computer instructions for building one or more connector stubs from said metamodel metadata.

41. (currently amended): The program product of claim 39 further comprising computer instructions to build a connector for carrying out the steps of:

- 1) retrieving connector metamodel metadata of respective source and target languages from the metamodel metadata repository;

- 2) populating the connector metamodels with metamodel ~~data~~metadata of each of the respective source and target languages from the metamodel metadata repository and invoking the retrieved, populated connector metamodels; and
- 3) converting the source language to the target language.

42. (currently amended): The program product of claim 41 wherein the metamodel metadata in the metamodel metadata repository comprises invocation metamodel metadata, application domain interface metamodel metadata, and type descriptor metamodel metadata.

43. (original): The program product of claim 42 wherein the invocation metamodel metadata is chosen from the group consisting of message control information, security data, transactional semantics, trace and debug information, pre-condition and post-condition resources, and user data.

44. (original): The program product of claim 42 wherein the application domain interface metamodel metadata comprises input parameter signatures, output parameter signatures, and return types.

45. (original): The program product of claim 42 wherein the application domain interface metamodel metadata further includes language metamodel metadata.

46. (currently amended): The program product of claim 45 wherein the language metamodel metadata includes mappings between the source and target languages.

47. (currently amended): The program product of claim 46 wherein the source language is object oriented, and the language metamodel metadata maps encapsulated objects into code and data.

48. (original): The program product of claim 46 wherein the language metamodel metadata maps object inheritances into references and pointers.

49. (currently amended): The program product of claim 43 wherein the type descriptor metamodel metadata defines physical realizations, storage ~~mapping~~ mappings, data types, data structures, and realization constraints.

50. (new): The program product of claim 39 wherein the source language is PL/I.

51. (new): The program product of claim 39 wherein the target language is PL/I.